<u>DISCLOSURE OF INFORMATION ON RADON HAZARDS</u> (For Residential Real Property Sales or Purchases)

Radon Warning Statement

Every buyer of any interest in residential real property is notified that the property may present exposure to dangerous levels of indoor radon gas that may place the occupants at risk of developing radon-included lung cancer. Radon, a Class-A human carcinogen, is the leading cause of lung cancer in non- smokers and the second leading cause overall. The Seller of any interest in residential real property is required to provide the buyer with any information on radon test results of the dwelling showing elevated levels of radon in the seller's possession.

The Illinois Emergency Management Agency (IEMA) strongly recommends ALL homebuyers have an indoor radon test performed prior to purchase or taking occupancy and mitigated if elevated levels are found. Elevated radon concentrations can easily be reduced by a qualified, licensed radon mitigator.

Seller's Disclosure (initial each of the following which applies)

(a) EPA or IEMA recommend present within the du		Action Le				
(b)all available record radon concentrations	s and rep	orts pert	taining to	rchas o ele	ser v evate	with ed
(c)	Seller ha		nowledge	of	elev	ated
(d)	Seller	has no	records	or	repo	rts
pertaining to elevat dwelling.	ed radon	concentr	ations	with	nin	the

Purchaser's Acknowledgment (initial each of the following which applies)

(e)				I	Purchaser	has	received	copies
	of	all	information	listed	above.			

(f)			Purchaser	has	received	the	IEMA
approved	Radon	Disclosure	Pamphlet				

Certification of Accuracy

The following parties have reviewed the information above and each party certifies, to the best of his or her knowledge, that the information he or she provided is true and accurate.

Seller Delhe Horles POA	Date $\frac{9/6/22}{}$
Seller	Date
Purchaser	Date
Purchaser	Date
Agent	Date
Agent	Date



Radon Testing Guidelines for Real Estate Transactions

ecause of the unique nature of real estate transactions, involving multiple parties and financial interests, the U.S. Environmental Protection Agency (U.S. EPA) designed special protocols for radon testing in real estate transactions. The Illinois Emergency Management Agency (IEMA)-Division of Nuclear Safety has adapted these protocols to conform with its radon regulations. These options are listed in simplified form in the table below.

Recommendations for Real Estate Transactions

IEMA strongly recommends ALL homebuyers have an indoor radon test performed prior to purchase or taking occupancy, and mitigated if elevated levels are found. It is not in the best interest of the buyer or seller to rely on a radon measurement performed by anyone other than a licensed measurement professional or Technician. Elevated radon concentrations can easily be reduced by a qualified, licensed radon mitigator.

Test Options for Real Estate Transactions

Conduct a short-term radon test in each of the lowest structural areas of the home. For example, if the house has one or more of the following foundation types, e.g., basement, crawl space, slab-on-grade, a testin each area is required for licensed professional measurements.

What to Look for in Short-Term Real Estate Testing Options				
Option Detector Location What to do Next				
Simultaneous Two short-term tests, 48 hours or longer, performed at the same time.	Two detectors, four incites apart, in each of the lowest structural areas suitable for occupancy.	Fix the home if the average of the two tests is 4 picoCuries per liter (pCi/L) or more.		
Continuous Monitor Test One test, 48 hours or longer, per- formed with an active continuous monitor that integrates and records radon levels hourly.	Continuous monitor placed in each of the lowest structural area suitable for occupancy.	Fix the home if the average radon level is 4 pG/L or more.		

Short-term tests may last between two and 90 days. Most last between two and seven days. Tests between seven and 90 days are usually impractical for real estate transactions. Examples of short-term detectors used in real estate testing include: activated charcoal canisters, cltarcoal liquid scintillation vials, electret chambers and continuous radon monitors.

If your tests don't agree, contact the IEMA-Division of Nuclear Safety

If your simultaneous or sequential tests are not in agreement (or if you're not sure whether or not they agree), contact the IE"MA-Division of Nuclear Safety Radon Program or your licensed radon measurement professional.



When do you average radon test results?

The only time radon test results can be averaged in a

The only time radon test results can be averaged is when two test results are placed simultaneously. Test results from different areas, such as above the crawl space and in the basement, are considered two different tests. Results are each independent of the other and are reported L,dependently, such as basement result of 4.2 pCi/L and family room over crawl space result of 6.1 pCi/L. With an elevated radon level in any one of the lowest structural areas, the recommendation is to fix the house.



Interference , with successful completion of a radon measurement is illegal in Illino is . Rev. 12 $\,9/2007$ (IEMA.018)

IEMA-Division of Nuclear Safety Recommendations for Real Estate Radon Measurements

Hire a licensed radon measurement professional.

Be sure that IEMA-Division of Nuclear Safety Radon Program radon testing protocols are followed.

Contact the IEMA-Division of Nuclear Safety Radon Program if you are uncertain about anything regarding radon testing. www.radon.illinois.gov

Disclosure of Radon Information

The Illinois Radon Awareness Act and the Illinois Real Property Disclosure Act requires that a seller of a home disclose information if aware of unsafe concentrations of radon in the home. The acts do not require that testing or remediation work be conducted. However, many relocation companies and lending institutions, as well as home buyers, request a radon test when purchasing a house. Sellers and brokers are cautioned to err on the side of full disclosure of material facts prior to entering into a purchase agreement

when Testing

Be aware that any test lasting less than a week requires closed-house conditions. Oosed-house conditions mean keeping all windows closed, keeping doors closed except for normal entry and exit, and not operating fans or other machines which bring air in from outside (except for fans that are part of a radon reduction system, or small exhaust fans that operate for only short periods of time).

• Before Testing: Begin closed-house conditions at least 12 hours before the start of the short-term test.

During Testing: Maintain closed-house conditions during the entire duration of the short term test, especially for tests less than one week in duration. Operate home heating or cooling systems normally during the test For tests

lasting less than one week, only operate air conditioning units that recirculate interior air.

Note that professional measurement licensees are required to post Radon Measurement in Progress Notifications at every building entry

v\lhere the test should be conducted

Place the detector or detectors in each lowest area suitable for occupancy, such as:

a family room, living room, den, playroom, bedroom, workshop, or exercise room; in the lowest level suitable for occupancy, even if it isn't currently used but could be, without renovating.

For instance, if the house has one or more of the following foundation types, e.g., basement, crawl space, slab-on-grade, a test should be performed in the basement and in at least one croom over the crawlspace and slab-on-grade area. If an elevated radon concentration is found and confirmed in one of these areas, fix the house.

DO NOT MEASURE:

- in the kitchen, laundry room and bathroom (because fan systems and humidity may affect some detectors); or
- in crawl spaces, on floor or wall cracks, or right next to a sump pump, as this may cause a false high reading.

The detector should be placed

- in an area where it, will not be disturbed;
- at least three feet from doors and windows to the outside;
- at least one foot from exterior walls:
- 20 inches to 6 feet from the floor;
- at least four inches away from other objects horizontally and directly above the detector;

away from drafts; and

four feet from heat, fireplaces, furnaces, and away from direct sunlight and areas of high humidity.

Iftlte test results show radon levels above 4 pCi/L

Contact the EMA-Division of Nuclear Safety Radon Program. Staff can provide names and addresses of professional radon mitigators who are trained to reduce radon concentrations. We also recommend that you see our web site www.radon.illinois.gov or contact the Radon Program for a copy of our brochure, LEMA-Division of Nuclear Safety Guide to RadrmMitigation.

After a radon reduction system is installed

Perform an independent short-term test to ensure that the reduction system is effective. Make sure the system is operating during the entire test.

The IEMA-Division of Nuclear Safety Radon Program can provide:

Information about radon and radon testing;

Names of licensed radon measurement professionals;

Names of licensed radon mitigation professionals trained to reduce radon.

Call the IEMA-Division of Nuclear Safety Radon Program at 1(800) 325-1245







ILLINOIS REALTORS® DISCLOSURE OF INFORMATION AND ACKNOWLEDGEMENT LEAD-BASED PAINT AND/OR LEAD-BASED PAINT HAZARDS



1/1

Lead Warning Statement

FORM 420 (05/2019) COPYRIGHT ILLINOIS REALTORS®

Every purchaser of any interest in residential real property on which a residential dwelling was built prior to 1978 is notified that such property may present exposure to lead from lead-based paint that may place young children at risk of developing lead poisoning. Lead poisoning in young children may produce permanent neurological damage, including learning disabilities, reduced intelligence quotient, behavioral problems, and impaired memory. Lead poisoning also poses a particular risk to pregnant women. The seller of any interest in residential real property is required to provide the buyer with any information on lead-based paint hazards from risk assessments or inspections in the seller's possession and notify the buyer of any known lead-based paint hazards. A risk assessment or inspection for possible lead-based paint hazards is recommended prior to purchase.

Property Address: 803 S Cherry St., O'Fallon, IL 62	269
Seller's Disclosure (initial)	
(a) Presence of lead-based paint and/or lead-base	ed paint hazards (check one below):
	ed paint hazards are present in the housing (explain):
. 🗸 🗀	
Seller has no knowledge of lead-based page 1	aint and/or lead-based paint hazards in the housing.
(b) Records and Reports available to the seller (ch	
 Seller has provided the purchaser with all lead-based paint hazards in the housing (available records and reports pertaining to lead-based paint and/or list documents below):
Seller has no reports or records pertaining housing.	to lead-based paint and/or lead-based paint hazards in the
Purchaser's Acknowledgment (initial)	
(c) Purchaser has received copies of all information	n listed above.
(d) Purchaser has received the pamphlet <i>Protect</i> Y	
(e) Purchaser has (check one below):	•
☐ Received a 10-day opportunity (or mutually of the presence of lead-based paint or lead	agreed upon period) to conduct a risk assessment or inspection d-based paint hazards; or
☐ Waived the opportunity to conduct a risk and/or lead-based paint hazards.	assessment or inspection for the presence of lead-based paint
Agent's Acknowledgment (initial)	
	obligations under 42 U.S.C. 4852d and is aware of his/her
Certification of Accuracy	
The following parties have reviewed the information above a have provided is true and accurate.	and certify to the best of their knowledge, that the information they
Seller Wello Hocker TOA Date 9/6/202	2 Purchaser Date
Seller Date	Purchaser Date
Agent Date	Agent Date
(This disclosure form should be attached to the Contract to Purchase	
and the state of t	00.7